

High-tech co-extruded and single-layer film suited for use in food-processing, for the lamination industry and the adhesive and silicon coating industry.

Our products for lamination are characterised by elevated sealability and hot tack for use on high-speed packaging lines.

Produced on dedicated lines protected against external contamination.

Elevated guarantee of homogeneity on treated side.



**FAMILY: LAMINATION**

Film produced on high-tech machines to guarantee excellent flatness and absence of gels.

<b>Properties</b>		<b>Units</b>	<b>Method</b>	<b>Value</b>		<b>Tol.</b>
<b>THICKNESS</b>		mm		<b>0,030</b>	<b>0,120</b>	+/- 10%
<i>Yield Stress</i>	L MD T TD	N	ASTM D 882	3,6 3,8	23,4 21,6	+/- 10%
<i>Tensile Strength</i>	L MD T TD	N	ASTM D 882	7 5,9	45 38	+/- 10%
<i>Ultimate Elongation</i>	L MD T TD	%	ASTM D 882	400 600	450 650	+/- 50
<i>Coefficient of friction</i>	STA DIN	-	ASTM D 1894	0,25 0,20	0,25 0,20	+/- 10%
<i>Corona treatment</i>	L MD	Dyne/cm	ASTM D 2578	46	46	+/- 2

**WIDTHS** from 760 mm to 2600 mm **THICKNESSES** from 30 my to 120 my

**Notice**

The descriptions and figures contained herein are provided to customers by way of a general information for the purposes the product is intended for. These reflect Crocco's knowledge at the time of publication. Since the acknowledged various product applications by customers cannot be controlled by Crocco S.p.A, in no circumstances may Crocco S.p.A. be held responsible for the results obtained from the customers manufacturing processes or for the product used in combination with other substances. All data, information and suggestions here enclosed are to be considered just as an indication. The company will reserve the right to modify the data sheets without any notice.