

TechnicalFilm

COATING FILM

High-tech co-extruded and single-layer film suited for use in food-processing, for the lamination industry and the adhesive and silicon coating industry.

Our products for lamination are characterised by elevated sealability and hot tack for use on high-speed packaging lines.

Produced on dedicated lines protected against external contamination.

Elevated guarantee of homogeneity on treated side.



COATING FILM
FAMILY: COATING

Film produced on high-tech machines to guarantee excellent flatness and absence of gels. Also features an elevated sealing temperature range and elevated hot tack.

<i>Properties</i>		<i>Units</i>	<i>Method</i>	<i>Value</i>		<i>Tol.</i>
THICKNESS		mm		0,055	0,075	+/- 10%
<i>Yield Stress</i>	L MD T TD	N	ASTM D 882	12 12	16 15	+/- 10%
<i>Tensile Strength</i>	L MD T TD	N	ASTM D 882	19,5 15	26 22,5	+/- 10%
<i>Ultimate Elongation</i>	L MD T TD	%	ASTM D 882	500 600	500 700	+/- 50
<i>Coefficient of friction</i>	STA DIN	-	ASTM D 1894	0,7 0,6	0,7 0,6	+/- 10%
<i>Corona treatment</i>	L MD	Dyne/cm	ASTM D 2578	-	-	-

LAIZES: de 760 à 2600 mm - **ÉPAISSEURS:** de 55 à 75 my

Notice

The descriptions and figures contained herein are provided to customers by way of a general information for the purposes the product is intended for. These reflect Crocco's knowledge at the time of publication. Since the acknowledged various product applications by customers cannot be controlled by Crocco S.p.A, in no circumstances may Crocco S.p.A. be held responsible for the results obtained from the customers manufacturing processes or for the product used in combination with other substances. All data, information and suggestions here enclosed are to be considered just as an indication. The company will reserve the right to modify the data sheets without any notice.